

EWP 15 HIGH EFFICIENCY

SELF-CONTAINED EMERGENCY LIGHTING
WEATHER & IMPACT RESISTANT
SLIM & ELEGANT



Technical Data

Mode of Operation	: Non-Maintained
Input Voltage	: 240V±10%, 50 Hz
Battery	: Hi-Temp. Nickel Cadmium Battery.
Charging Current	: 100mA (Nominal)
Lamp Used	: 15 x Super Bright White LED.
Operating Temperature	: 0°C to 60°C
Charger	: Fully Automatic Constant Current. Solid-State Electronics Provide High Reliability with Trickle Charge-Facility.
Indication	: Red L.E.D. "On" Indicates Charging Equipped with Push Test-Switch to Simulate Power Failure.
Backup Time	: 3 Hours Duration.
Construction	: Injection Moulded Fire-Retardant Polycarbonate Housing with Rear Knockout Cable Entry. : Injection Moulded Fire-Retardant Polycarbonate Diffuser. : Housing and Diffuser are made of Corrosion Resistant Material Luminaries can be Reinforced with Ø 2.5mm Neoprene Seal for Jetproof, Dustproof (IP 65) and Vandaproof.
Weight	: \approx 1.2kg
#Warranty	: 5 Years
Compliance	: Malaysia Standards MS-619, IP-65.
Protection	: Low-Voltage Cut-Off to Prevent Over-Discharge of Battery.

Wall Mounting

Dimension in mm Tolerance: ± 0.03

